

Introducing the Autobag® 500™ Bagging System – The new flagship in bag-packaging machinery optimises reliability, flexibility and ergonomics

The Autobag® 500™ bagger is a technologically-advanced, automatic filling and sealing machine designed for reliability, flexibility and optimising packaging throughput. Capable of cycling at rates over 100 bags per minute, this system was designed to maximise machine uptime while lowering total cost of ownership.

State-of-the-art engineering has led to an innovative, inherently safe design. No light curtains or double palm switches are required to achieve safe operation for hand-load operations. This revolutionary new approach provides unobstructed access to the open bag, facilitating faster, more ergonomic loading.


The system features a simple design with very few moving parts, reducing lifetime cost and improving uptime. Servo-driven web controls along with job storage capabilities reduce the amount of bags in queue, eliminating waste and decreasing changeover time.

Flexibility has been built into the system, allowing the Autobag 500 to meet the needs of any loading area. Capable of being configured for left or right-hand access to the HMI, cycle switch and roll loading provides seamless integration into any operation. The system can also be networked for full pack station integration to facilitate central monitoring, and the extraction of productivity information that can be manipulated for detailed analysis.

When used with genuine Autobag pre-opened bags-on-a-roll, the Autobag 500 ushers in the next evolution of high-quality, reliable and flexible bag packaging, backed by the industry's most comprehensive engineering and field service network.

Markets Served

- Aerospace & Defence
- Apparel & Accessory Packaging
- Automotive
- Electronics
- Hardware & Fasteners
- Healthcare
- Hobby & Craft
- Household Products
- Personal Products
- Pet Products
- Toys



Easily integrates with inline printers, counters, scales, and conveyors for semi- to fully-automatic bagging



Modular components and dedicated service access simplify maintenance and repairs to maximise uptime



AutoTouch™ Control Screen accesses operator tutorials, help system, on-board diagnostics, and performance monitoring



Multi-position unwind with tension control simplify changeover

Features and Benefits

More Options

More bag size options; from 51 mm W x 63.5 mm L to 305 mm W x 508 mm L supported (914 mm long unsupported)

Streamlined

Processor-controlled servo motors, Ethernet-capable networking, and flexible mechanical design streamline integration

Compact

Compact footprint minimises floor space

Adjustable

Simple height adjustment and castors for operator comfort and portability

Flexible

Adjustable pass-through up to 127 mm for maximum flexibility and packaging efficiency



Largest Supply

We maintain over 100 styles of stock bags and manufacture custom bags that include printing in up to 10 colours and a variety of special features



Ensures Consistent Quality

Newly designed bag sealer area combined with improved temperature control and optional seal flatteners ensure consistent, high-quality seals



Optional Additions

- Range of In-Feed Funnels
- Seal Flatteners
- Raised Unwind
- SimpleCount™ Counting System
- Product Load Tray

Technical Information



Weight	159 kg
Electrical	Universal Input: 110V to 240V VAC, 50/60 Hz Power Consumption: 1500 Watts (VA) max
Air Feed	5 CFM/80 psi of clean, dry air
Pass-Through	127 mm max
Bag Thickness	27.7 – 101.6 µm
Bag Sizes	W 51 to 305 mm L* 63.5 mm to 508 mm <small>*There are two versions, Long and Short. Long configuration min length is 127 mm. Short min length is 63.5 mm.</small>
Weight Capacity	Up to 2.3 kg (with load shelf)



System-matched Bags



Service & Support



Custom Engineering & Integration

+91 22 25649652 info@autobag.co.in autobag.co.in

Automated Packaging Systems India, 65, Shanti Industrial Estate, S.N. Road
Mulund (West), Mumbai – 400080, Maharashtra, India

Automated
PACKAGING SYSTEMS

India