

Introducing the Autobag® 850S™ Mail Order Fulfilment System – The most technologically-advanced system for mail order fulfilment bagging

The new Autobag® 850S™ bagger is uniquely designed to provide enhanced packaging productivity for mail order fulfilment applications. Capable of running bags up to 559 mm wide, this system features a breakthrough bag opening technology that securely grips and holds the open bag in place. This creates a large, square opening (up to 279 x 279 mm) that allows for easy loading of single or multi-line orders.

Next-bag-out printing is achieved with an advanced thermal transfer imprinter positioned directly over the next bag to be loaded. This ensures accuracy and efficiency in fulfilment applications that require frequent product and label changeovers, and prevents product queuing.

State-of-the-art engineering has resulted in a system that is inherently safe. The Autobag 850S eliminates the need for bulky guarding or devices required for safe operation. This unobstructed access makes loading ergonomic and improves operator throughput.

When used with genuine Autobag pre-opened bags-on-a-roll, the Autobag 850S ushers in the next evolution of high-quality, reliable and flexible mail order fulfilment packaging, backed by the industry's most comprehensive engineering and field service network.

Markets Served

- Single or multi-line mail order fulfilment
- Prescription-by-mail fulfilment
- Apparel
- Fashion Accessories
- Sporting Goods
- Footwear



Next-bag-out printing prevents product queuing and reduces waste



Simple bag threading for easy changeover to keep production lines running smoothly



Programmable pass-through up to 279 mm for maximum flexibility



Unobstructed access minimises guarding for easy access to the open bag

Features and Benefits

Extra Large Bag Sizes

Capable of running bags up to 550 mm wide for large products and multi-line orders

High Quality Seals

Coordinated seal flattener for wrinkle free seals

Continuous Film Control

A sophisticated tension control unit centres and monitors the position of the film throughout the entire bagging process

Compact

Compact footprint minimises floor space

Flexible

Easily integrates with third-party systems

Adjustable

Simple height adjustment and castors for operator comfort and portability

Breakthrough Technology

Advanced bag opening system minimises bag size and facilitates multi-line orders



Easy Loading

Modular bag storage shelf that speeds bag changeovers



Intuitive Interface


AutoTouch™ Control Screen accesses operator tutorials, help system, on-board diagnostics, data retrieval, and performance monitoring. It features menu or graphic-based selection options



Optional Additions

- Rear Takeaway Conveyor (Optional label up mechanism)
- Side Exit Takeaway Conveyor

Technical Information



Weight	268 kg
Electrical	110/220 VAC switchable 50/60 Hz, 1,800 watts continuous
Air Feed	5 CFM/80 psi of clean, dry air
Pass-Through	Up to 279 mm
Bag Thickness	28 to 100 µm
Bag Sizes	W 254 to 559 mm L 254 to 914 mm
Weight Capacity	Up to 5 kg (with load shelf)



System Matched Materials



Service & Support



Custom Engineering & Integration

+91 22 25649652 info@autobag.co.in autobag.co.in

Automated Packaging Systems India, 65, Shanti Industrial Estate, S.N. Road
Mulund (West), Mumbai – 400080, Maharashtra, India

Automated
PACKAGING SYSTEMS

India