

Introducing the Autobag® 600™ Wide Bagging System – Bringing flexibility, reliability and high productivity to large bag packaging applications

The Autobag® 600™ bagger is a technologically advanced, wide automatic filling and sealing machine designed for reliability, flexibility and optimising packaging throughput. Capable of cycling at speeds over 65 bags per minute, this system delivers maximum machine uptime while lowering total cost of ownership.

State-of-the-art engineering has led to an innovative, inherently safe design. No light curtains or double palm switches are required to achieve safe hand-load operation. The Autobag 600 is configurable for left- or right-hand access to the HMI, cycle switch and bag-loading area, improving ergonomics and operator productivity.

Flexibility has been built into the system, allowing the Autobag 600 to meet the needs of any large packaging operation. The open design makes this bagger highly compatible with Autobag and third-party counters, scales and infeeds. The Autobag 600 can also be networked to facilitate full pack station integration and central monitoring. When integrated with the AutoLabel 600™ inline printer, a complete Print-and-Pack™ station is achieved.

A straightforward, simple design with very few moving parts reduces lifetime cost and improves reliability, while on-board diagnostics and modular components simplify maintenance.

When used with genuine Autobag pre-opened bags-on-a-roll or bags-in-a-box, the Autobag 600 ushers in the next evolution of high-quality, reliable and flexible wide bag packaging, backed by the industry's most comprehensive engineering and field service network.

Markets Served

- Aerospace & Defence
- Apparel & Accessory Packaging
- Automotive
- Electronics
- Hardware & Fasteners
- Healthcare
- Hobby & Craft
- Household Products
- Personal Products
- Pet Products
- Toys



Easily integrates with inline printers, counters, scales and conveyors for semi- to fully-automatic bagging



Multi-position unwind with tension control simplifies changeover



AutoTouch™ Control Screen accesses operator tutorials, help system, on-board diagnostics, and performance monitoring



406-mm-wide bag loading area is ideal for large or bulk products

*Autobag 600 with optional AutoLabel 600 printer shown

Features and Benefits

Streamlined

Processor-controlled servo motors, ethernet-capable networking and flexible mechanical design streamline integration

Compact

Compact footprint minimises floor space

Adjustable

Simple height adjustment and castors for operator comfort and portability

Configuration Options

A 45-degree tilt option is available for orienting long or delicate products



Flexible

Adjustable pass-through up to 152 mm for maximum flexibility and packaging efficiency



Ensures Consistent Quality

Newly designed bag-sealer area combined with improved temperature control and optional seal flatteners ensure consistent, high-quality seals



Largest Supply

We maintain over 100 styles of stock bags and manufacture custom bags that include printing in up to 10 colours and a variety of special features



Optional Additions

- Range of Infeed Funnels
- Seal Flatteners
- Raised Unwind
- SimpleCount™ Counting System
- Product Load Tray
- Bags-in-a-box Adapter

Technical Information



Weight	186 kg
Electrical	Universal Input: 110V to 240V VAC, 50/60 Hz Power Consumption: 1500 Watts (VA) max
Air Feed	5 CFM/80 psi of clean, dry air
Pass-Through	152 mm max
Bag Thickness	28 – 102 µm
Bag Sizes	W 102 to 406 mm L 140 to 686 mm (914 mm L unsupported)
Weight Capacity	Up to 3.6 kg (with load shelf)



System-matched Materials



Service & Support



Custom Engineering & Integration

+91 22 25649652 info@autobag.co.in autobag.co.in

Automated Packaging Systems India, 65, Shanti Industrial Estate, S.N. Road
Mulund (West), Mumbai – 400080, Maharashtra, India

 **Automated**
PACKAGING SYSTEMS

India